

Lateral packer

made of high quality rubber with fabric insert

- for the rehabilitation of service connections
- temperature range from -20° to +80° C
- with eyelets at both ends



Part Number	Nominal Size [MM]	Product Normal Length [MM]	Cylinder- Length [MM]	Min. Pipe Diameter [MM]	Min. contact Length [MM]	Required Inflation Pressure [Bar]	Product Weight [Kg]
LP253506	DN 25 - 35	760	600	20	520	3,0	0,3
LP253510	DN 25 - 35	1.160	1.000	20	920	3,0	0,5
LP253515	DN 25 - 35	1.660	1.500	20	1.420	3,0	0,7
LP253520	DN 25 - 35	2.160	2.000	20	1.920	3,0	0,9
LP253525	DN 25 - 35	2.660	2.500	20	2.420	3,0	1,1
LP253530	DN 25 - 35	3.160	3.000	20	2.920	3,0	1,3
LP253540	DN 25 - 35	4.160	4.000	20	3.920	3,0	1,7
LP253550	DN 25 - 35	5.160	5.000	20	4.920	3,0	2,1
LP355006	DN 35 - 50	760	600	25	520	3,0	0,4
LP355010	DN 35 - 50	1.160	1.000	25	920	3,0	0,6
LP355015	DN 35 - 50	1.660	1.500	25	1.420	3,0	0,8
LP355020	DN 35 - 50	2.160	2.000	25	1.920	3,0	1,1
LP355025	DN 35 - 50	2.660	2.500	25	2.420	3,0	1,3
LP355030	DN 35 - 50	3.160	3.000	25	2.920	3,0	1,6
LP355040	DN 35 - 50	4.160	4.000	25	3.920	3,0	2,1
LP355050	DN 35 - 50	5.160	5.000	25	4.920	3,0	2,6
LP507006	DN 50 - 70	760	600	33	450	3,0	0,5
LP507010	DN 50 - 70	1.160	1.000	33	850	3,0	0,7
LP507015	DN 50 - 70	1.660	1.500	33	1.350	3,0	1,0
LP507020	DN 50 - 70	2.160	2.000	33	1.850	3,0	1,3
LP507025	DN 50 - 70	2.660	2.500	33	2.350	3,0	1,6
LP507030	DN 50 - 70	3.160	3.000	33	2.850	3,0	1,9
LP507040	DN 50 - 70	4.160	4.000	33	3.850	3,0	2,5
LP5007050	DN 50 - 70	5.160	5.000	33	4.850	3,0	3,1
LP7010006	DN 70 - 100	760	600	42	470	3,0	0,5
LP7010010	DN 70 - 100	1.160	1.000	42	870	3,0	0,8
LP7010015	DN 70 - 100	1.660	1.500	42	1.370	3,0	1,2
LP7010020	DN 70 - 100	2.160	2.000	42	1.870	3,0	1,5
LP7010025	DN 70 - 100	2.660	2.500	42	2.370	3,0	1,9
LP7010030	DN 70 - 100	3.160	3.000	42	2.870	3,0	2,2
LP7010040	DN 70 - 100	4.160	4.000	42	3.870	3,0	2,9
LP7010050	DN 70 - 100	5.160	5.000	42	4.870	3,0	3,6
LP8012506	DN 80 - 125	760	600	54	450	3,0	0,5
LP8012510	DN 80 - 125	1.160	1.000	54	850	3,0	0,8
LP8012515	DN 80 - 125	1.660	1.500	54	1.350	3,0	1,2
LP8012520	DN 80 - 125	2.160	2.000	54	1.850	3,0	1,5
LP8012525	DN 80 - 125	2.660	2.500	54	2.350	3,0	1,9
LP8012530	DN 80 - 125	3.160	3.000	54	2.850	3,0	2,2
LP8012540	DN 80 - 125	4.160	4.000	54	3.850	3,0	2,9
LP8012550	DN 80 - 125	5.160	5.000	54	4.850	3,0	3,6

LP10015006	DN 100 - 150	760	600	63	400	2,5	1,1
LP10015010	DN 100 - 150	1.160	1.000	63	800	2,5	1,7
LP10015015	DN 100 - 150	1.660	1.500	63	1.300	2,5	2,5
LP10015020	DN 100 - 150	2.160	2.000	63	1.800	2,5	3,2
LP10015025	DN 100 - 150	2.660	2.500	63	2.300	2,5	4,0
LP10015030	DN 100 - 150	3.160	3.000	63	2.800	2,5	4,7
LP10015040	DN 100 - 150	4.160	4.000	63	3.800	2,5	6,2
LP10015050	DN 100 - 150	5.160	5.000	63	4.800	2,5	7,7
LP15020006	DN 150 - 200	760	600	112	400	2,5	1,3
LP15020010	DN 150 - 200	1.160	1.000	112	800	2,5	2,0
LP15020015	DN 150 - 200	1.660	1.500	112	1.300	2,5	2,3
LP15020020	DN 150 - 200	2.160	2.000	112	1.800	2,5	2,8
LP15020025	DN 150 - 200	2.660	2.500	112	2.300	2,5	4,5
LP15020030	DN 150 - 200	3.160	3.000	112	2.800	2,5	5,4
LP15020040	DN 150 - 200	4.160	4.000	112	3.800	2,5	7,1
LP15020050	DN 150 - 200	5.160	5.000	112	4.800	2,5	8,8
LP15025006	DN 150 - 250	760	600	112	400	2,5	1,3
LP15025010	DN 150 - 250	1.160	1.000	112	800	2,5	2,0
LP15025015	DN 150 - 250	1.660	1.500	112	1.300	2,5	2,3
LP15025020	DN 150 - 250	2.160	2.000	112	1.800	2,5	2,8
LP15025025	DN 150 - 250	2.660	2.500	112	2.300	2,5	4,5
LP15025030	DN 150 - 250	3.160	3.000	112	2.800	2,5	5,4
LP15025040	DN 150 - 250	4.160	4.000	112	3.800	2,5	7,1
LP15025050	DN 150 - 250	5.160	5.000	112	4.800	2,5	8,8
LP20030010	DN 200 - 300	1.160	1.000	148	720	2,0	2,7
LP20030015	DN 200 - 300	1.660	1.500	148	1.220	2,0	3,8
LP20030020	DN 200 - 300	2.160	2.000	148	1.720	2,0	5,0
LP20030030	DN 200 - 300	3.160	3.000	148	2.720	2,0	7,3
LP20030040	DN 200 - 300	4.160	4.000	148	3.720	2,0	9,6
LP20030050	DN 200 - 300	5.160	5.000	148	4.720	2,0	11,9
LP30040015	DN 300 - 400	1.660	1.500	210	1.220	1,5	7,0
LP30040020	DN 300 - 400	2.160	2.000	210	1.720	1,5	9,1
LP30040030	DN 300 - 400	3.160	3.000	210	2.720	1,5	13,3
LP30040040	DN 300 - 400	4.160	4.000	210	3.720	1,5	17,5
LP30040050	DN 300 - 400	5.160	5.000	210	4.720	1,5	21,7
LP40050015	DN 400 - 500	1.660	1.500	300	1.210	1,0	8,6
LP40050020	DN 400 - 500	2.160	2.000	300	1.710	1,0	11,2
LP40050030	DN 400 - 500	3.160	3.000	300	2.710	1,0	16,4
LP40050040	DN 400 - 500	4.160	4.000	300	3.710	1,0	21,6
LP40050050	DN 400 - 500	5.160	5.000	300	4.710	1,0	26,8
LP50060015	DN 500 - 600	1.660	1.500	350	1.200	1,0	11,3
LP50060020	DN 500 - 600	2.160	2.000	350	1.700	1,0	14,7
LP50060030	DN 500 - 600	3.160	3.000	350	2.700	1,0	21,5
LP50060040	DN 500 - 600	4.160	4.000	350	3.700	1,0	28,3
LP50060050	DN 500 - 600	5.160	5.000	350	4.700	1,0	35,1